

ARDEX X 78™

MICROTEC® Fiber Reinforced, Semi-Pourable, Tile and Stone Mortar

ARDEX X 78 is a high performance, microfiber reinforced, semi-pourable, tile and stone mortar especially formulated for horizontal, large format tile installations.

Use for:

Porcelain, quarry, ceramic, mosaic and most natural stone tiles.



Key Features

- Superior bond strength and highly flexible for excellent shear resistance
- Ideal for interior and exterior; floor and horizontal surface applications in high-traffic areas
- Very easy to mix and apply, creamy smooth semi-pourable consistency
- Use over in-floor heating systems
- Special additives virtually eliminate the chance of efflorescence

Installation

- **Packaging:** 40 lb. (18 kg) White or Gray
- **Coverage:**
 - 1/4" x 1/4" x 1/4" Sq. Notch Trowel
105 sq. ft (9.75 sq. m)
- **Open time:** 60 minutes- double the ISO standard
- **Pot life:** 4 hours
- **Working time:** up to 15 minutes
- **Time to grout floors:** 24 hours

Performance

VOC: 0



Refer to the technical data sheet at www.ardexamericas.com or call 888-512-7339 prior to installation. For free ARDEX product training click on ARDEX Academy.

For easy-to use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google Play.



888-512-7339
+1-724-203-5000
www.ardexamericas.com

AF225 12/15

ARDEX MORTARS